

## Fitop Electric Chain Hoist Product Specification

Model	Code		Nominal Capacity (kg)	Lifting Speed (m/min)				STD. Lift L (m)	Load Chain Fall Lines
	Single Speed	Dual Speed		50 Hz		60 Hz			
				Single Speed	Dual Speed	Single Speed	Dual Speed		
CS451	CS451031	CS451033	1500	9.5	9.5/3.2	114	11.4/3.8	3	1
CS601	CS601031	CS601033	2000	8.0	8.0/2.7	96	9.6/3.2		1
CS751	CS751031	CS751033	2500	7.3	7.3/2.4	88	8.8/2.9		1
CS452	CS452031	CS452033	3000	4.8	4.8/1.6	57	5.7/1.9		2
CS752	CS752031	CS752033	5000	3.7	3.7/1.2	44	4.4/1.5		2
CS753	CS753031	CS753033	7500	2.4	2.4/0.8	29	2.9/1.0		3
CS754	CS754031	CS754033	10000	3.7	3.7/1.2	44	4.4/1.5		4

Model	Lifting motor 3 phase		Duty Rating (ED%/S/H)	Net Weight (kg)		Chain Dia./Pitch Mm/mm	Weight in kg for addition 1m of lift	Push button H (m)	Power Cable Supply Length (m)
	Output (kW)			Single Speed	Dual Speed				
	Single Speed	Dual Speed							
CS451	3.75	3.75/1.25	40/250	118	122	10.0/30.0	2.18	3.1	1.5
CS601	3.75	3.75/1.25		118	122	10.0/30.0	2.18		
CS751	4.50	4.50/1.50		124	125	11.2/34.0	2.73		
CS452	4.75	4.75/1.25		132	136	10.0/30.0	4.36		
CS752	4.50	4.50/1.50		146	147	11.2/34.0	5.46		
CS753	4.50	4.50/1.50		146	147	11.2/34.0	5.46		
CS754	4.50	4.50/1.50		146	147	11.2/34.0	5.46		